


<b>Product</b>	Duo Peel PLPE-700P														
<b>Description</b>	Duo Peel PLPE-700P is a two piece liner that provides a clean peel seal to PP/PE containers. This liner will separate leaving a foil seal across the neck and backing reseal board in the cap														
<b>Composition</b>	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Material</th> <th style="text-align: left;">Metric</th> </tr> </thead> <tbody> <tr> <td>White Pulp</td> <td>0.7000 mm</td> </tr> <tr> <td>Wax Layer</td> <td>Application Specific</td> </tr> <tr> <td>Aluminium Foil</td> <td>0.0250 mm</td> </tr> <tr> <td>Sealing Layer</td> <td>0.0450 mm</td> </tr> <tr> <td><b>Overall</b></td> <td><b>0.7700 mm</b></td> </tr> </tbody> </table>	Material	Metric	White Pulp	0.7000 mm	Wax Layer	Application Specific	Aluminium Foil	0.0250 mm	Sealing Layer	0.0450 mm	<b>Overall</b>	<b>0.7700 mm</b>		
Material	Metric														
White Pulp	0.7000 mm														
Wax Layer	Application Specific														
Aluminium Foil	0.0250 mm														
Sealing Layer	0.0450 mm														
<b>Overall</b>	<b>0.7700 mm</b>														
<b>FDA Status :</b>	21 CFR 177.1210 "Closures with sealing gaskets for food containers"														
<b>GTR Oxygen</b>	< 0.01 g/m2 .day	<b>MVTR</b>	<0.01cc/m2 .day												
<b>Storage and Usage</b>	The ideal temperature for storage and transport is 15 - 30 Centigrade and 40 - 60% relative humidity without high pressure. Failure to store the goods at the recommended storage condition may lead to unexpected failure of the material and not covered by any implied or actual warranty. A full copy of the recommended storage and transport condition are available from the Selpac office.														

Selpac materials are compliant with limitations of heavy metals in packaging per CONEG & EU 94/62/EC

